



## NT 65/2 Ap

The NT 65/2 Ap is a powerful, 2-motor wet and dry vac for professional applications. The suction power remains nearly constant due to the efficient cleaning of the flat pleated filter by blasts of air.

#### 1 Hose and bend attachment

Convenient suction hose and bend attachment for easy transport and storage.

#### 3 Integrated drain hose (oil-resistant)

Convenient suction hose and bend attachment for easy transport and

### 2 On-board storage

■ The large on-board storage space on the casing head ensures that tools and accessories are always stored and close to hand.

### 4 ApClean (semi-automatic filter cleaning system)

- The free filter means that the user can work for long intervals without interruption.
- Optimum suction power with high efficiency.

# **TECHNICAL DATA AND EQUIPMENT**





## NT 65/2 Ap

- Semi-automatic filter cleaning
- Flat pleated filter (dust class M)
- Drain hose and push handle

Technical data		
Order no.		1.667-291.0
EAN code		4039784727281
Air flow rate	I/s	2 x 74
Vacuum	mbar / kPa	254 / 25.4
Container capacity	1	65
Max. rated input power	W	max. 2760
Standard nominal width		ID 40
Cable length	m	10
Sound pressure level	dB(A)	73
Container material		plastic
Number of motors		2
Frequency	Hz	50-60
Voltage	V	220-240
Weight	kg	20
Dimensions (L × W × H)	mm	600 × 480 × 920

Equipment					
Suction hose	m	4	Push handle		
Suction Tube	piece(s) / m	2 × 0.5 / Metal	Safety class		II
Filter bag		Paper	Steering roller stop		
Wet and dry floor nozzle	mm	360	Maintenance-free suction turbines	piece(s)	2
Crevice nozzle					
Drain hose (oil-resistant)					
Automatic switch-off at max. filling quantity		•			
Flat pleated filter		Paper			
Bend					
Filter cleaning		ApClean (semi-automatic filter cleaning system)			
Sturdy bumper					
Included in the scene of supply					

■ Included in the scope of supply.

## NT 65/2 AP 1.667-291.0



























									$\top$
		Order no.	Quantity	ID	Length	Width	Price	Description	
Bend, plastic									
DN 40 bend	1	2.889-171.0	1 piece(s)	ID 40				Bend for the new clip system in nominal size DN 40.	
Plastic bend	2	5.031-718.0	1 piece(s)	ID 35				Plastic bend (DN 35) with C-35 clip system. For all industria	ı
								single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	
Bend, plastic, electrically conducti-	3	5.031-939.0	1 piece(s)	ID 35				Electrically conductive plastic bend (DN 35) with C-35 clip	_
ve								system. For all industrial single-motor NT 361 to NT 611 Eco models.	
	4	5.032-427.0	1 piece(s)	ID 40				Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	
Bend	5	2.889-148.0	1 piece(s)	ID 35				Ergonomic bend for the new clip system. With airflow con-	
Floor nozzles								trol slide, in an antistatic design.	_
Multi-purpose nozzle, wet/dry	6	6.903-018.0	1 piece(s)	ID 40		370 mm		All-purpose aluminium nozzle with 370 mm working width.	
ment perpese mezzie, welyary		0.303 010.0	1 prece(s)	15 10		0,0,1,,,,		With height-adjustable side rollers, brush strips (6.903-	
								064.0) and oil-resistant squeegees (6.903-081.0). Only for	
								NT vacuum cleaners.	_
	7	6.906-383.0	1 piece(s)	ID 40		450 mm		All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips	
								(6.903-065.0) and oil-resistant squeegees (6.906-146.0).	
								Only for NT vacuum cleaners.	
	8	6.906-384.0	1 piece(s)	ID 35		370 mm		All-purpose aluminium nozzle (DN 35) with 370 mm wor-	
								king width. With height-adjustable side rollers, brush strips	
								(6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	
Crevice nozzles		l						Only for the vaccom cicaners.	
Crevice nozzle	9	6.900-385.0	1 piece(s)	ID 35	210 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and	
								corners. Length: 210 mm.	╨
	10	6.900-922.0	1 piece(s)	ID 35	500 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and	
	11	6.905-817.0	1 piece(s)	ID 40	400 mm			corners. Length: 370 mm.  Metal crevice tool (DN 40) for vacuuming in crevices and	+
	11	0.303 017.0	1 piece(s)	15 40	400 11111			corners. Length: 400 mm.	
Suction tubes, stainless steel									
Set suction tube stainless steel NW40 55	12	2.889-194.0	1 piece(s)	ID 40	550 mm			Stainless steel suction tube set (2 × 0.55 m)	•
Suction tube	13	6.902-081.0	1 piece(s)	ID 40	0.5 m			Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.	
	14	6.906-531.0	1 piece(s)	ID 40	1 m			Stainless steel suction tube (DN 40, 1.0 m) only suitable for	+
	1	0.500 551.0	1 prece(s)	15 10	1			NT vacuum cleaners.	
	15	6.902-154.0	1 piece(s)	ID 35	0.5 m			0.5 m long stainless steel suction tube (ID 35) for wet and	
								dry vacuum cleaners. Ideal for frequent wet vacuuming	
Complete suction hoses (clip system	n)	l					l	applications and for vacuuming corrosive components.	_
Suction hose DN 40, length 4 m	16	2.889-138.0	1 piece(s)	ID 40	4 m			4 m suction hose with new bayonet and clip fastener.	
Suction hose	17	4.440-678.0	1 piece(s)	ID 40	4 m			4 m electrically non-conductive suction hose with bend,	╁
			, , , , ,					bayonet at vacuum end and C 40 clip connection at accessor	- 🗆
								ry end. Without module.	$\perp$
Suction hose + PFC module	18	4.440-679.0	1 piece(s)	ID 40	4 m			4 m electrically non-conductive suction hose with bend	
								(C-DN 40) and module (4.060-474.0), bayonet at vacuum end and C 35 clip connection at accessory end.	
Suction hose + PFC module, electri-	19	4.440-728.0	1 piece(s)	ID 40	4 m			With bend and module (4.060-533.0), electrically conducti-	1
cally conductive								ve.	

<sup>■</sup> Included in the scope of supply. 

Available accessories.





























									Г
		Order no.	Quantity	ID	Length	Width	Price	Description	
Flat pleated filter, PES									
Flat pleated filter, PES	20	6.904-284.0	1 piece(s)					Flat filter (PES) - BIA-(U,S,G,C) dust class M: rotproof polyes-	
								ter fleece, ideal for wet use and abrasives. Standard for NT	
Flat pleated filter, PTFE								72/2 Eco Tc.	L
Flat pleated filter, PTFE	21	6.907-449.0	1 piece(s)					Polyester fleece with PTFE coating, dust class M, for Tact <sup>2</sup>	
nat preated inter, i ii 2		0.507 1.5.0	1 prece(s)					vacuum cleaners. Particularly suitable for very adhesive	
								materials.	
Fabric filter		ı	1	1					
Membrane filter	22	6.904-282.0	1 piece(s)					Polyester needle fleece membrane/fabric filter - BIA-C -,	_
								washable up to 40°C, metal fibres for earthing. Suitable for	
HEPA, dust class H filter		<u>I</u>						virtually all industrial two-motor NT vacuum cleaners.	_
HEPA flat pleated filter	23	6.904-364.0	1 piece(s)			l		HEPA surface filter - dust class H (H 14) - with glass-fibre	i
Tier what pleated their	23	0.504 504.0	1 piece(s)					layers increases filter capacity when vacuuming health-	
								endangering and carcinogenic dust.	
Plastic sacks for dust-free disposal				,					
Plastic sack for dust-free disposal	24	6.900-698.0	10 piece(s)					PE plastic sack.	
Wet filter bag		1	1						
Wet filter bag	25	6.904-252.0	5 piece(s)					Approved for dust class L, general cleaning, wet and dry,	
Bends, stainless steel								tear-resistant.	L
Bend, stainless steel, ID 35	26	6.903-141.0	1 piece(s)	ID 35	1	ı	1	Stainless steel and crooked, ID 35	
Bend, stainless steel, ID 40	27	6.902-079.0	1 piece(s)	ID 40				Stainless steel and crooked, ID 40	
Bends, metal	21	0.302 073.0	1 piece(s)	110 40				Statiliess steel and crooked, 15 40	Ľ
Bend, metal	28	6.900-519.0	1 piece(s)	ID 35				Robust, chromium-plated metal bend (DN 35), can be used	
Bella, Metal	20	0.500 515.0	1 piece(s)	15 33				instead of a plastic bend (with clip system adapter 5.407-	Е
								112.0; C 35-DN 35, plastic, el.).	
	29	6.900-276.0	1 piece(s)	ID 40				Robust, chromium-plated metal bend (DN 40), can be used	
								instead of a plastic bend (with clip system adapter 5.407-	
Car cleaning nozzles		<u> </u>				]		111.0; C 40-DN 40, plastic, el.).	L
Car nozzle	30	6.900-952.0	1 piece(s)	ID 40		90 mm		Angled, flat, plastic car vacuuming tool with about 90 mm	
Car riozzic	50	0.300 332.0	1 piece(s)	15 40		30 11111		working width. Only for NT vacuum cleaners.	
Rubber suction tools, nose 45°									
Rubber suction tool, nose 45°	31	6.902-104.0	1 piece(s)	ID 35	220 mm			45° rubber suction nozzle (DN 35), oil-resistant and suitable	
								for vacuuming machines. Only for NT vacuum cleaners.	L
	32	6.902-105.0	1 piece(s)	ID 40	220 mm			45° rubber suction nozzle (DN 40), oil-resistant and suitable	
Pipe dusting nozzles		l						for vacuuming machines. Only for NT vacuum cleaners.	L
Pipe brush 35/100	33	6.903-035.0	1 piece(s)	ID 35		l		Plastic, pipe diameter 100 mm	
Pipe brush 35/200	34	6.903-036.0	1 piece(s)	ID 35				Plastic, pipe diameter 200 mm	
Suction tubes, metal			F(a)	1		1		The same and	۲
Suction tube	35	6.900-514.0	1 piece(s)	ID 35	0.5 m			Chromium-plated metal suction tube (DN 35, 1x0.5 m),	Ì
			, , , ,					standard for virtually all single-motor industrial NT vacuum	
								cleaners.	L
Repair kits		ı			ı	ı			
Repair kit, C 40	36	2.639-873.0	1 piece(s)	ID 40				Repair set (C40) includes threaded hose adapters (without	_
								bayonet adapter) for industrial NT vacuum cleaners with clip system.	L
		 □ Available as	1 .				1	ayatem.	_































		Order no.	Quantity	ID	Length	Width	Price	Description	
Repair kit, ID 61	37	2.862-038.0	1 piece(s)	ID 61				Suction hose repair kit. Optional for all NT 65/2 and 72/2, NT 993 I, NT 802 I.	
Suction hoses (clip system)			·						
Suction hose	38	6.906-279.0	1 piece(s)	40	10 m			10 m standard suction hose without bend and adapter. With bayonet at vacuum end and C 40 clip connection at accessory end.	_
	39	6.906-321.0	1 piece(s)	40	4 m			4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	
	40	6.906-714.0	1 piece(s)	40	4 m			With bayonet and clip connection.	
	41	6.906-546.0	1 piece(s)	40	4 m			Electrically conductive, 4 m suction hose with bayonet and (40 clip connection. Without bend and adapter.	
	42	6.906-635.0	1 piece(s)	40	16 m			With bayonet and clip connection.	
	43	6.906-877.0	1 piece(s)	40	10 m			Suction hose with bayonet coupling, electrically conductive.	
Suction hoses complete			_						
Suction hose, complete	44	4.440-264.0	1 piece(s)	ID 61	4 m			4-m standard suction hose with DN 61 bayonet connector at the device end and DN 61 tapered connector at the accessory end.	
	45	4.440-467.0	1 piece(s)	ID 61	10 m			10-m standard suction hose with DN 61 bayonet connector at the device end and DN 61 tapered connector at the accessory end.	
Suction hose, complete, oil-resistant	46	4.440-613.0	1 piece(s)	ID 61	4 m			Oil-resistant.	
Suction hose, complete, electrically conductive	47	4.440-616.0	1 piece(s)	ID 61	4 m			Electrically conductive.	
Suction hose, complete	48	4.440-263.0	1 piece(s)	ID 40	4 m			Electrically non-conductive 4.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.	<u> </u>
	49	4.440-303.0	1 piece(s)	ID 40	4 m			Oil-resistant	
	50	4.440-463.0	1 piece(s)	ID 40	10 m			Electrically non-conductive 10.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.	
	51	4.440-466.0	1 piece(s)	ID 40	10 m			Electrically conductive, 10.0m, ID 40	
Suction hose, complete, oil-resistant	52	4.440-612.0	1 piece(s)	ID 40	10 m			Oil-resistant.	
Connecting sleeves								,	Ļ
Adapter, ID 32/35, with internal thread	53	6.902-077.0	1 piece(s)	ID 32				Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	r
Connecting adapter, ID 40, with internal thread	54	6.900-286.0	1 piece(s)	ID 40				Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.	
Connecting sleeve, ID 61, with female thread	55	6.902-078.0	1 piece(s)	ID 61				For connecting 2 suction hoses, thread on both sides	
Extension hoses (clip system)									
Extension hose	56	6.906-344.0	1 piece(s)	ID 40	2.5 m			2.5 m electrically non-conductive standard extension hose for all C-40 hoses with clip system.	
Other		1	_						
CS 40 Me	57	2.863-026.0	1 piece(s)					The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.	
Y-adapter kit									
Y-adapter kit	58	2.637-217.0	1 piece(s)	ID 35				Plastic distributor - suitable for NT vacuum cleaners.	
								•	_

# NT 65/2 AP 1.667-291.0





























		1	1			1	1		_
		Order no.	Quantity	ID	Length	Width	Price	Description	
Connection adapter C ID (clip to con	e), ele	ectrically conduc	tive						
Connection adapter C DN 35	59	5.407-112.0	1 piece(s)	ID 35				C 35 hose connector for DN 35 accessory, electrically con-	
	00							ductive.	
Connection adapter C DN 40	60	5.407-109.0	1 piece(s)	ID 40				Electrically conductive adapter (C 40) with DN 35 connec-	
								tion for connecting DN 35 accessories to an industrial C 40	
								or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	
	61	5.407-111.0	1 piece(s)	ID 40				C 40 hose connector for DN 40 accessory, electrically con-	
								ductive.	
Connection adapter for power tools	, clip-	on, electrically c	onductive						
Connection adapter for power	62	5.453-042.0	1 piece(s)	ID 35				3-way plastic adapter. For DN 26 to DN 36. For connecting	
tools, C 35, electrically conductive								power tools to an industrial C or C-DN 35 suction hose.	
								Suitable for NT vacuum cleaners.	┺
	63	5.453-048.0	1 piece(s)	ID 35				Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically	
								conductive. Only NT vacuums.	Ľ
Connection Adaptor for power	64	5.453-049.0	1 piece(s)	ID 35				Inner Ø 28.6 mm, outer Ø 37.3 mm/ 38.8 mm, el. Only NT-	
tools, C 35, electrically conductive								vacuums.	F
Connection adapter for power	65	5.453-050.0	1 piece(s)	ID 35				Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically	
tools, C 35, electrically conductive								conductive. Only NT vacuums.	_
Connection Adaptor for power	66	5.453-051.0	1 piece(s)	ID 35				Inner Ø 32 mm, outer Ø 39 mm, el. Only NT-vacuums.	
tools, C 35, electrically conductive	67	5.453-052.0	1 piece(s)	ID 35				Inner Ø 28 mm, outer Ø 34 mm/ 38.8 mm, el. Only NT-	
								vacuums.	_
Adapter for electric power tools, sc	1	1	1	1		1			
Adapter for electric power tools,	68	5.453-016.0	1 piece(s)	ID 35				3-way plastic adapter with fitting instructions. For DN 26 to	
screwable, ID 35		F 4F2 026 0	4 -:(-)	ID 25				DN 36. For connecting to an industrial DN 35 suction hose.	-
	69	5.453-026.0	1 piece(s)	ID 35				Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.	
	70	6.902-059.0	1 piece(s)	ID 35				Electrically conductive power tool adapter, threaded. Inter-	
	74	6.002.005.0	4 -:(-)	ID 25				nal diameter: 32 mm.External diameter: 39 mm.	₩
	71	6.902-095.0	1 piece(s)	ID 35				2-way power tool adapter, threaded. For connecting to an	
								industrial DN 35 suction hose. Internal diameter: 28 mm. External diameter: 34 mm and 38.8 mmSuitable for NT	
								vacuum cleaners.	
Expansion pieces (tube -> nozzle)		-				1		vacouri creariers.	
Adapter	72	5.453-019.0	1 piece(s)	ID 40				From DN 40 to DN 61: Plastic adapter (electrically non-	
Adapter	12	3.433 013.0	1 piece(s)	15 40				conductive). Suitable for NT vacuum cleaners.	
Reducing sleeves								conductive). Softable for five vaccome cleaners.	
Reducer	73	5.407-108.0	1 piece(s)	ID 40				Threaded reducer - from C-40 to DN 35. Suitable for NT	
Nedocci	/3	3.407 100.0	1 piece(s)	15 40				vacuum cleaners.	
Reduction bushing	74	5.407-113.0	1 piece(s)	ID 40				Reducer (C 40 to C 35) for connecting accessories with C-35	$\vdash$
reduction bosining	, ¬	3.407 113.0	I piece(s)	15 40				clip connection to suction hoses with C 40 clip system.	
Reducers (tube -> nozzle)		'	1					1	
Reducer	75	6.902-017.0	1 piece(s)	ID 40				Reducer for accessory extension. Ideal for accessories with	
	, ,							DN 35 connecting cone in combination with accessories with	10
								DN 40 connecting cone.	1
Reducer from ID 35 to ID 32	76	6.902-072.0	1 piece(s)	ID 35				Reducer with internal connecting cone DN 32. Ideal for	
								accessories from the industrial vacuum cleaner range in	
			<u> </u>					combination with industrial NT vacuum cleaners.	
Reduction/expansion adapter kit									
Set of reducers / adapter sleeves	77	2.860-117.0	1 piece(s)					DN 40/35, DN 35/32 (tube -> nozzle), plastic.	

## NT 65/2 AP 1.667-291.0











		Order no.	Quantity	ID	Length	Width	Price	Description	
Target-group-specific accessory k	its for v	acuum cleaners	,						
Professional cleaning kit	78	2.637-353.0		ID 40				Individual parts: Suction hose 4 m (4.440-263.0), bend, metal (6.900-276.0), suction tube 2 x 0.5 m, metal (6.900-275.0), grout nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).	
Car cleaning accessory kit	79	2.862-166.0		ID 35				Target group-specific accessory nozzles in DN 35 for interior cleaning of vehicles, upholstery & fixtures.	
Swarf kit	80	2.640-760.0		ID 61				Target group-specific robust connection set in DN 61 for cleaning in conjunction with oil-resistant suction hose and rubber nozzle.	
Modification kit, non-conductive	media				•		•		
Attachment kit, non-conductive media Tact² + Ap	81	2.642-602.0	1 piece(s)					For switching off when vacuuming non-conductive fluids such as oils and greases	

<sup>■</sup> Included in the scope of supply. 

Available accessories.

## NT 65/2 AP 1.667-291.0





		Order no.	Length	Colour	Quanti- ty	Price	Description	
Miscellaneous								
Extension cable	1	6.647-022.0	20 m		1 piece(s)		Extension cable, 20 m, 3x1.5 mm <sup>2</sup> . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	

<sup>■</sup> Included in the scope of supply. 

□ Available accessories.